



代号	名称	截面图	材料	压力	温度	圆周速度	特点
VB	外露单唇 无弹簧油封		橡胶+骨架	0	NBR -40至100	≤6	外圆周面为精加工骨架, 可装配硬基座,无防尘唇 不能承压密封
					FKM -20至200	≤10	
KB	外露双唇 无弹簧油封		橡胶+骨架	0	NBR -40至100	≤6	外圆周面为精加工骨架, 可装配硬基座,有防尘唇 不能承压密封
					FKM -20至200	≤10	

d	D	H	d	D	H	d	D	H	d	D	H	d	D	H
7	16	6	20	47	6	30	50	8	40	65	5	60	75	6
7	20	5	22	32	5	30	52	5	40	65	6	60	78	7
8	14	4	22	35	5	30	55	5	42	55	6	60	82	6
10	20	4	22	38	6	30	56	5	42	55	7	60	82	9
10	25	5	22	38	8	32	45	5	42	60	7	60	85	6
12	22	4	22	42	5	32	52	5	42	65	9	60	90	7
12	25	5	24	38	5	32	52	8	45	60	6	62	85	6
12	30	6	24	40	6	35	45	5	45	62	6	63	80	7
14	24	4	25	35	5	35	47	5	45	62	7	64	82	7
14	24	6	25	38	5	35	50	5	45	65	5	70	90	10
14	28	5	25	40	5	35	50	6	45	68	6	70	92	7
15	25	4	25	40	6	35	52	5	45	68	9	75	100	7
15	30	4	25	45	5	35	55	5	45	72	6	75	100	8
15	30	5	25	45	7	35	55	8	48	65	7	80	95	6
15	30	7	25	47	5	35	60	5	48	65	9	80	100	7
15	32	6	25	47	6	35	88	6	48	70	6	85	110	8
15	35	6	25	50	5	38	50	5	50	65	6	95	120	8
16	24	4	26	48	6	38	52	6	50	68	7	100	125	8
16	28	4	27	47	8	38	55	6	50	72	6	105	150	12
17	30	5	28	40	5	38	55	8	50	80	6	110	150	15
17	32	6	28	45	6	38	58	8	50	80	7	115	140	13
18	30	5	28	47	5	38	64	5	52	70	7	120	150	14
19	35	6	28	48	5	40	52	5	55	70	6	140	165	15
19	40	6	28	50	6	40	55	5	55	72	7	140	170	10
19	40	6	30	40	5	40	58	6	55	74	6	165	190	13
20	26	6	30	42	5	40	60	5	56	70	6	195	220	15
20	32	5	30	45	6	40	62	5	58	75	7	200	230	16
20	35	6	30	46	5	40	62	6	58	80	5			
20	40	5	30	50	5	40	62	8	58	80	9			